

SIGNBRIDGE PRO

60 W LED driver. Model: BPSE-60-12V.1



FEATURES

- Metal housing design with functional ground
- Built-in active PFC function
- IP68 rating for indoor or outdoor installations
- Typical lifetime $\geq 70,000$ hours
- 7 years warranty

CONFORMITY & STANDARDS

EMC Emission:

- compliance to EN55015

EMC Immunity:

- EN55015
- EN61547
- EN61000-3-2
- EN61000-3-3
- CB
- ENEC
- CE-LVD:
 - IEC/EN61347-1
 - IEC/EN61347-2-13
 - UL8750
 - UL1310



GENERAL SPECIFICATIONS

EFFICIENCY	$\geq 86\%$ (230 VAC)
COLD START	3000 ms (230 VAC)
OPERATING CONDITIONS	$-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$; 20 ~ 95% humidity
STORAGE CONDITIONS	$-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$; 10 ~ 95% humidity
IP CLASS	IP68
PROTECTIONS INCLUDED	Over voltage Over current Short circuit Over temperature
WARRANTY	7 years, $\geq 70\,000$ h

QUANTITY OF DRIVERS PER CIRCUIT BREAKER

CIRCUIT BREAKER OF TYPE B 16 A	CIRCUIT BREAKER OF TYPE C 25 A
5 units (230 VAC)	8 units (230 VAC)

DIMENSIONS (MM)



Balt led

INPUT

INPUT VOLTAGE RANGE	200 – 240 Vac; 50 – 60 Hz
MAX INPUT AC CURRENT	0.5 A Max
MAX INRUSH CURRENT	≤ 50 A
POWER FACTOR	≥ 0.90 (230 VAC)

OUTPUT

OUTPUT CURRENT	5 A
OUTPUT VOLTAGE	12 V
OUTPUT POWER	60 W

ORDERING INFORMATION

SKU	UNIT NET WEIGHT, G	UNIT DIMENSIONS (LxWxH), MM	STATUS
BPSE-60-12V.1	450.0	160 x 44 x 34mm	PRE-ORDER*

* For pre-order products MOQ and precise lead time, contact your country manager.