

SIGNBRIDGE PLUS

150 W LED driver. Model: BPSP-150-12V.1



FEATURES

- Metal housing design with functional ground
- Built-in active PFC function
- IP68 rating for indoor or outdoor installations
- Typical lifetime $\geq 50,000$ hours
- 5 years warranty

CONFORMITY & STANDARDS

EMC Emission:

- compliance to EN55015

EMC Immunity:

- EN55015
- EN61547
- EN61000-3-2
- EN61000-3-3
- CB
- ENEC
- CE-LVD:
 - IEC/EN61347-1,
 - IEC/EN61347-2-13,
 - UL8750
 - UL1310




GENERAL SPECIFICATIONS

EFFICIENCY (TYP.)	$\geq 92\%$ (230 VAC)
COLD START	3000 ms (230 VAC)
OPERATING CONDITIONS	$-40^{\circ}\text{C} \sim +45^{\circ}\text{C}$; 20 ~ 95% humidity
STORAGE CONDITIONS	$-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$; 10 ~ 95% humidity
IP CLASS	IP68
PROTECTIONS INCLUDED	Over voltage Over current Short circuit Over temperature
WARRANTY	5 years, $\geq 50,000$ h

QUANTITY OF DRIVERS PER CIRCUIT BREAKER

CIRCUIT BREAKER OF TYPE B 16 A	CIRCUIT BREAKER OF TYPE C 25 A
3 units (230 VAC)	8 units (230 VAC)

DIMENSIONS (MM)



Balt led

INPUT

INPUT VOLTAGE RANGE	200 – 240 Vac; 50 – 60 Hz
MAX INPUT AC CURRENT	2.1 A Max
MAX INRUSH CURRENT	≤ 70 A
POWER FACTOR	≥ 0.95 (230 VAC)

OUTPUT

OUTPUT CURRENT	12.5 A
OUTPUT VOLTAGE	12 V
OUTPUT POWER	150 W

ORDERING INFORMATION

SKU	UNIT NET WEIGHT, G	UNIT DIMENSIONS (LxWxH), MM	STATUS
BPSP-150-12V.1	916.0	202 x 66 x 34	AVAILABLE