



HERONLUX SM

PRODUCT DESCRIPTION

HeronLux SM - surface mounted downlight luminaire, an ideal solution for your office lighting. Due to its versatility, HeronLux luminaires are also perfect to illuminate such spaces as corridors, shopping centers, hallways and etc.

APPLICATION

- Offices
- Hallways
- Shopping centres
- Technical rooms
- Common rooms
- Showrooms

FEATURES & BENEFITS

- Available options from 1294 lm up to 1888 lm
- IP20 protection class
- 5 year warranty
- Easy installation


HERONLUX SM

GENERAL INFORMATION

| | |
|--------------------|--------------------------------|
| SUPPLY VOLTAGE | 220 - 240 V, 50-60 Hz |
| POWER FACTOR | 0.90 |
| EFFICACY | 108 – 126 lm/W |
| CCT | 4000 K ± 150 K (natural white) |
| CRI | >80 |
| BEAM ANGLE | 90° |
| IP CLASS | IP20 |
| RECOMMENDED HEIGHT | from 2 to 6 meters |
| OPERATING TEMP. | -15 °C ~ +40 °C |
| STORAGE TEMP. | +5 °C ~ +50 °C |
| LIFETIME | L80B10 50 000 h (Ta +25 °C) |
| MOUNTING OPTIONS | surface mounted |
| CERTIFICATION | CE compliant |
| WARRANTY | 5 years |



LIGHT DISTRIBUTION GRAPH



— C0-180 - - - C90-270 90°

ORDERING INFORMATION

| SKU | POWER, W | LUMEN OUTPUT, LM | DIMENSIONS, MM | WEIGHT, KG |
|-----------------------|----------|------------------|-----------------------|------------|
| BDNP-SM-D150A90840I12 | 12 ± 3% | 1294 ± 3% | Face/height: Ø150*120 | 1.10 |
| BDNP-SM-D190A90840I15 | 15 ± 3% | 1888 ± 3% | Face/height: Ø190*120 | 1.51 |