



# HERONLUX UG SM



## PRODUCT DESCRIPTION

HeronLux UG SM - surface mounted downlight luminaire, an ideal solution for your office lighting. Due to its versatility, HeronLux luminaires are also perfect to illuminate such spaces as corridors, shopping centers, hallways and etc.

## APPLICATION

- Offices
- Hallways
- Shopping centres
- Technical rooms
- Common rooms
- Showrooms

## FEATURES & BENEFITS

- IP65 protection class
- 5 year warranty
- Easy installation

# HERONLUX UG SM

## GENERAL INFORMATION

SUPPLY VOLTAGE	220 - 240 V, 50-60 Hz
POWER FACTOR	0.95
EFFICACY	84 -104 lm/W
CCT	4000 K ± 150 K (natural white)
CRI	>80
BEAM ANGLE	60°
IP CLASS	IP65
RECOMMENDED HEIGHT	from 2 to 6 meters
OPERATING TEMP.	-15 °C ~ +40 °C
STORAGE TEMP.	+5 °C ~ +50 °C
LIFETIME	L80B50 100 000 h (Ta +25 °C )
MOUNTING OPTIONS	surface mounted
CERTIFICATION	CE compliant
WARRANTY	5 years



## ORDERING INFORMATION

SKU	POWER, W	CRI	LUMEN OUTPUT, LM	DIMENSIONS, MM
BDNP-R6-A60940E25-W-DA-SM	25	90	2100	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60940E15-W-DA-SM	15	90	1350	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60940E25-B-DA-SM	25	90	2100	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60940E15-B-DA-SM	15	90	1350	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60840E25-W-DA-SM	25	80	2100	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60840E15-W-DA-SM	15	80	1350	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60840E25-B-DA-SM	25	80	2100	Skersmuo/aukštis: Ø140*130
BDNP-R6-A60940E15-B-DA-SM	15	80	1350	Skersmuo/aukštis: Ø140*130