



# HERONLUX UG

## PRODUCT DESCRIPTION

HeronLux UG downlight luminaire – an ideal solution for your office lighting. Due to their versatility, HeronLux luminaires are also perfect to illuminate such spaces as corridors, shopping centres, exhibition halls and etc. Designed for recessed ceiling.

## APPLICATION

- Offices
- Hallways
- Shopping centres
- Technical rooms
- Common rooms
- Showrooms

## FEATURES & BENEFITS

- IP65 protection class
- DALI control available
- 5 year warranty
- Easy installation

# HERONLUX UG

## GENERAL INFORMATION

SUPPLY VOLTAGE	220 – 240 V, 50-60 Hz
POWER FACTOR	0.95
EFFICACY	84 - 104 lm/W
CCT	4000 K ± 150 K (natural white)
CRI	>80
BEAM ANGLE	60°
IP CLASS	IP65
RECOMMENDED HEIGHT	from 2 to 6 meters
OPERATING TEMP.	-15 °C ~ +40 °C
STORAGE TEMP.	+5 °C ~ +50 °C
LIFETIME	L80B50 100 000 h (Ta +25 °C )
MOUNTING OPTIONS	recessed
CERTIFICATION	CE compliant
WARRANTY	5 years
OPTIONAL FEATURES	DALI



## ORDERING INFORMATION

SKU	POWER, W	CRI	LUMEN OUTPUT, LM	DIMENSIONS, MM	DALI FEATURE
BDNP-R6-A60940E25-W-DA	25	90	2100	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60940E15-W-DA	15	90	1350	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60940E25-B-DA	25	90	2100	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60940E15-B-DA	15	90	1350	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60840E25-W-DA	25	80	2100	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60840E15-W-DA	15	80	1350	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60840E25-B-DA	25	80	2100	Face/height: Ø190*100 Cut hole: Ø170	+
BDNP-R6-A60840E15-B-DA	15	80	1350	Face/height: Ø190*100 Cut hole: Ø170	+

